



(10) International Publication Number
WO 2004/095833 A1

PCT

(43) International Publication Date
4 November 2004 (04.11.2004)

(51) International Patent Classification⁷: H04N 5/335, 5/32

(21) International Application Number: PCT/JP2004/005654

(22) International Filing Date: 20 April 2004 (20.04.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data: 2003-117238 22 April 2003 (22.04.2003) JP

(71) Applicant (for all designated States except US): CANON KABUSHIKI KAISHA [JP/JP]; 3-30-2, Shimomaruko, Ohta-ku, Tokyo 1468501 (JP).

(72) Inventor; and

(72) Inventor; and
(75) Inventor/Applicant (for US only): YAGI, Tomoyuki

[JP/JP]; c/o CANON KABUSHIKI KAISHA, 3-30-2,
Shimomaruko, Ohta-ku, Tokyo 1468501 (JP).

(74) Agents: OKABE, Masao et al.; No. 602, Fuji Bldg., 2-3, Marunouchi 3-chome, Chiyoda-ku, Tokyo 1000005 (JP).


(81) **Designated States** (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) **Designated States (unless otherwise indicated, for every kind of regional protection available):** ARIPO (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR,

[Continued on next page]

(54) Title: PHOTOELECTRIC CONVERSION DEVICE AND RADIATION PHOTOGRAPHY APPARATUS

(57) Abstract: A sensor lower electrode of a MIS type photosensor is connected to a gate line distributed in a next line in a scanning direction through a refreshing capacitor. The MIS type photosensors of an (n-1)-th line are refreshed on the basis of an ON/OFF operation of TFTs accompanying a reading operation for a pixel column of an n-th line to thereby allow the refresh operation to be carried out every scanning line. Thus, it is possible to prevent a moving image from becoming unnatural due to the refresh operation as in the background art.



WO 2004/095833 A1